

# RL 4000 FLOODLIGHT SYSTEM



**COLEMAN**  
Engineering

*simple, available and cost effective™*



## **Economical and Effective Jobsite Lighting**

The Coleman Rite-Lite RL 4000 light tower provides cost effective mobile, trailer-mounted floodlighting for nighttime maintenance, construction, mining and emergency municipal work. Check these features:

- Dual self braking winch design easily and quickly raises 30 ft. (9.1 m) 360 degree rotating tower to provide 4000 Watts of light, enough to illuminate 5-7 acres.
- Operation is a quiet 71 DBA at 23 ft. (7m) and the unit will run more than 60 hours per tank of fuel.
- More than 60 hours of run time per tank of fuel.
- 3 cylinder diesel engine powers a brushless self regulated type generator. A 2/3 load to horsepower match helps ensure reliable, trouble-free operation.
- Centerpoint lifting bracket and fork lift pockets make transport easy. Compact design allows up to 10 units per truck load.
- Other features contributing to dependable performance and long service life include high temperature and low oil pressure shutdowns and durable, fade resistant polyester powder coat finish.

Products shown may have optional equipment.

# RL 4000 FLOODLIGHT SYSTEM



**COLEMAN**  
Engineering

*simple, available and cost effective™*



## Other performance-proven RL 4000 features

- In travel position, the Coleman Rite-Lite RL 4000 is only 54" (136 cm) wide, 167" (424 cm) long.
- Operation is simple with basic, user friendly control panel.

## Worldwide Distribution Network Provides Parts and Service

With a network of factory-trained distributors and dealers in many of the major markets around the world, Coleman Engineering can provide parts and service assistance to help keep downtime at a minimum. Coleman Engineering products also carry a full-year limited warranty on parts and labor.

### RL 4000 Specifications and Dimensions

Lighting system, type	Metal halide w/core and coil ballast
Wattage	4000W
Initial lumens	440,000
Light coverage, acres	5-7
Tower height	30' (9.1 m)
Engine type & model	Kubota/D905
Generator type	4 pole, brushless and self regulated
Continuous rating	6,000 Watts
Fuel tank capacity	30 gal. (114 l)
Fuel consumption @ full load	.5 gph
Unit dBA at 23 feet	71 dBA
Overall length	167" (424 cm)
Overall width, travel position	54" (137 cm)
Overall height, travel position	56" (142 cm)
Total weight, no fuel	1800 lbs. (816 kg)

We reserve the right to amend these specifications at any time without notice. The only warranty applicable is our standard written warranty applicable to the particular product and sale. We make no other warranty, expressed or implied.

For more information, product demonstration, or details on purchase, lease and rental plans, please contact your local Coleman Engineering Distributor.



**TEREX**  
LIGHT CONSTRUCTION

**Coleman Engineering**  
835 Hwy. 178 E. • Holly Springs, MS 38634  
662-252-5252 • Fax: 662-252-7373  
Call toll-free: 1-800-228-6444

[www.terex.com](http://www.terex.com)